

# SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

## **SIPCOLITE ALUMINIUM PAINT**

Sipcolite Aluminum Paint is a two-pack general purpose metallic aluminum paint. It gives excellent corrosion resistance properties. Sipcolite Aluminum Paint produces a beautiful, glossy, metallic finish of brilliant quality and great durability. Aluminum paint find application in iron towers, pipes electric poles, steel structures et al. Its protective and decorative nature make it excellent for top coats over primed metals and wooden surfaces.

<ul style="list-style-type: none"><li>• Packaging</li></ul>	<ul style="list-style-type: none"><li>• Two Pack System</li></ul>
<ul style="list-style-type: none"><li>• Application</li></ul>	<ul style="list-style-type: none"><li>• Brushing or Spraying</li></ul>
<ul style="list-style-type: none"><li>• Drying Time</li></ul>	<ul style="list-style-type: none"><li>• Hard Dry: Within 4 Hrs</li></ul>
<ul style="list-style-type: none"><li>• Shade</li></ul>	<ul style="list-style-type: none"><li>• Metallic Aluminum</li></ul>
<ul style="list-style-type: none"><li>• Covering Capacity</li></ul>	<ul style="list-style-type: none"><li>• 30-33 Sqm per ltr per coat</li></ul>
<ul style="list-style-type: none"><li>• Finish</li></ul>	<ul style="list-style-type: none"><li>• Bright &amp; Smooth Metallic finish</li></ul>
<ul style="list-style-type: none"><li>• Heat Resistance</li></ul>	<ul style="list-style-type: none"><li>• 250°C</li></ul>
<ul style="list-style-type: none"><li>• Shelf Life</li></ul>	<ul style="list-style-type: none"><li>• As long as container is firmly sealed and stored in good condition the material can be kept life long without deterioration. Due to lower flash point it should be stored at cool places and away from direct heat</li><li>• Mixed paint should be consumed within 24 hrs</li></ul>
<ul style="list-style-type: none"><li>• Directions</li></ul>	<ul style="list-style-type: none"><li>• The surface should be free from rust, grease, oil, moisture and loose matter. No primer/surfacer is normally required but if necessary due to surface defects Sipcolite Speed Coat Primer Surfacer Grey or Sipco Brown Metal Primer Q/D RP-4 may be used. Painted articles if required to be warped in paper should be done after overnight drying.</li></ul>