

Phn: +91-8009079988, 8009079977

Email: info@singhalpaints.com

SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

SIPCO N.C. SANDING SEALER

Singhal Paints Sipco NC Sanding Sealer is a single pack Nitro Cellulose based quick drying wood coating. It is an affordable, fast drying, easy to apply and sand, base coat for NC and melamine based top coats.

• Surfaces to be Painted	:Wooden furniture which are not subject to outdoor exposure. It is also well suited for finishing of less exposed surfaces such as the interior of drawers, cup boards etc.
• Viscosity of Application	:(a) Brushing-55 to 60 seconds. :(b) Spraying-30 to 35 seconds at a pressure of 3.5 Kg/CM ² , 40-50 p. s.i.
• Thinner Recommended	:NC Thinner
• Methods of Application	:By Brush, Conventional spray and by cloth
• Covering Capacity (on prepared smooth mild steel surface)	:8 to 10 sq. mt/ltr per coat (depending upon the application and coating thickness)
• Drying Time	:Surface Dry-Less than 15 minutes. Sanding Dry: 1 hour. (Drying will depend upon the ambient temperature and humidity.)
• Flash Point	:Above 25°C
• Directions for Use	: Ensure that the surface is free from rust, grease, moisture & loose particles. Clean the surface by rough sanding with emery paper 180 and wipe clean. If the wood is oily, wipe down well with a suitable solvent. Thin down the NC sanding sealer with NC thinner to the required application consistency.
• Shelf Life	Minimum 12 Months in unopened containers

The information given here is given in good faith but without warranty, since conditions of use are beyond our control.