

Phn: +91-8009079988, 8009079977

Email: info@singhalpaints.com

SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

Sipcolite Red Oxide Zinc Chromate Metal Primer

Sipcolite Red Oxide Zinc Chromate Metal Primer RP-5 is based on a combination of special synthetic resins medium and is a universal primer suitable for air drying as well as stoving process. It can be applied by brush, spray or dipping. It has better water, corrosion and rust creep resistance, excellent adhesion and flexibility. It gives semi glossy look. This primer will not be lifted when coated with stoving enamels having moderately powerful solvents.

• Surface to be Painted	:Ferrous.
• Colour	: Red Oxide
• Viscosity of Supply	:100 seconds on Ford Cup B4 at 30°C.
• Application Viscosity	: Spray : 40 seconds at Ford Cup B4 at 30°C. Dipping : 30-40 seconds at Ford Cup B4 at 30°C.
• Stoving Schedule	: 100°C. for 30 minutes. (Airdrying-Overnight)
• Application	: By Spray/Dipping/Brushing.
• Finish	: Smooth and semi glossy
• Covering Capacity	:10-12 Sqr. Meter/Litre
• Flash Point	:Above 30°C.

The information given here is given in good faith but without warranty, since conditions of use are beyond our control.