

Phn: +91-8009079988, 8009079977

Email: info@singhalpaints.com

# SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

## **Sipcolac Yellow Zinc Chromate Metal Primer**

Sipcolac Yellow Zinc Chromate Metal Primer is based on a special Synthetic Resin medium and formulated with Zinc Chrome as rust inhibiting pigment. It has good water & corrosion resistance and excellent adhesion and flexibility. It dries fast and can be both brushed and sprayed.

It is ideal for use as a primer for ferrous and non-ferrous metals.

• Surfacer to be painted	: Steel, Aluminium or Galvanized Steel and other non-ferrous metals
• Viscosity of Supply	: 100 seconds by Ford Cup B4 at 30°C.
• Shade visible	: Yellow
• Viscosity of application	: Brushing 40 to 45 seconds. Spraying 25 to 30 seconds. at a pressure 3.5 Kg./Cm. <sup>2</sup> (40-45 psi)
• Thinner recommended	: MTO
• Drying time	: Surface dry within 3 hour. Hard dry overnight
• Finish	: Matt.
• Covering capacity	: 10-12 square meters per litre per coat depending on the surface.
• Directions for use	: Ensure that the surface to be painted is free of grease, rust, moisture and loose matter. After drying of the Primer/Surfacer and prior to the application of finishing paint, smooth the primed surface with 240 emery paper.

The information given here is given in good faith but without warranty, since conditions of use are beyond our control.