

Phn: +91-8009079988, 8009079977

Email: info@singhalpaints.com

SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

Sipcolac Premium Knifing Putty

Sipcolac Premium Knifing Putty Grey is based on special Synthetic resins and may be air dried or stoved & dries hard and easy in cutting, involving no strain. It has butter-like consistency & is easy in application.

It does not affect the gloss or other properties of finishing coat enamel applied over it. It is recommended for use on Metallic Surfacers, for filling of dents, and other surface defects. Adding 1 kg putty in 1 kg whiting is recommended for softer cutting.

• Areas of Application	: Ferrous Metal.
• Method of Application	: Knifing.
• Shade available	: Grey
• Consistency of supply	: Smooth Paste
• Drying Time	:Surface dry-less than 30 minutes. Hard dry-Less than 12 hours.
• Finish	: Smooth and matt.
• Thinner recommended	: Mineral Turpentine oil.
• Directions for use	: Ensure that the surface is free from moisture and loose matter. Metal surface should be primed suitably prior to the application of Sipcolac Knifing Putty. Deep dents should not be filled at a stretch but in thin layers.

The information given here is given in good faith but without warranty, since conditions of use are beyond our control.