

Phn: +91-8009079988, 8009079977

Email: info@singhalpaints.com

SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

Sipcolite A/D Knifing Putty

Sipcolite Knifing Putty Grey is based on special Synthetic resins and may be air dried or stoved & dries hard and easy in cutting, involving no strain. It has butter-like consistency & is easy in application.

It does not affect the gloss or other properties of finishing coat enamel applied over it. It is recommended for use on Metallic Surfacers, for filling of dents, and other surface defects. Adding 1 kg putty in 1/2 kg whiting is recommended for softer cutting.

• Areas of Application	: Ferrous Metal.
• Method of Application	: Knifing.
• Shade available	: Grey
• Consistency of supply	: Smooth Paste
• Drying Time	:Surface dry-less than 30 minutes. Hard dry-Less than 12 hours.
• Finish	: Smooth and matt.
• Thinner recommended	:Mineral Turpentine oil
• Directions for use	: Sand the surface with Emery paper No. 180. Apply a coat of suitable primer (Sipcolite White Primer for wood, Sipcolite R.P.5 for metallic) depending on the surface of application and allow it to dry for 6-8 Hrs. Apply the putty with a putty knife, filling deep dents with thin layers of the paste. Allow a drying time of 6-8 hrs between coats. Apply a coat of primer before application of finish coats.

The information given here is given in good faith but without warranty, since conditions of use are beyond our control.