

Phn: +91-8009079988, 8009079977

Email: info@singhalpaints.com

SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

SIPCOLAC SATIN FINISH

Sipcolac Satin Finish Enamel is formulated to give a smooth Satin finish on wooden and metallic surfaces. Sipcolac Satin Finish has good flow and yields an attractive, durable, velvety and practical, satin finish which is easy to clean and maintain.

• Surface to be painted	:Metallic & Wooden Surfaces
• Method of Application	:Brush or Spray
• Shades Available	:As per our Satin Finish shade card
• Viscosity of Supply	: 90 Seconds by Ford Cup B4 at 30°C.
• Viscosity of application	:Spraying-30 - 40 seconds at a pressure 3.5 Kg/Cm ² (40-45 psi)
• Thinner recommended	:Upto 25% by volume
• Drying time	:Surface dry-30 min Recoat: Min 1 Hr.
• Finish	:Velvety & Eggshell. An experienced applicator can yield a very smooth eggshell finish.
• Covering Capacity	:15-17 Square meters per litre per coat depending on the surface.
• Flash Point	:Above 30°C
• Direction for use	:Ensure that surface to be painted is free of grease, rust, moisture and loose matter. After drying of the Primer/Surfacer and prior to the application of finishing paint, wet rub the primer with 240 abrasive paper.

The information given here is given in good faith but without warranty, since conditions of use are beyond our control.