

SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

Sipcolite Pink Surfacer

Sipcolite Pink Surfacer is based on synthetic resins and is an ideal surfacer for new wood. It has filling properties and give the right surfacer for taking synthetic enamels.

It is formulated specially to prevent the sinkage of gloss that appears when a synthetic is applied directly on wood.

• Surfacers to be Painted	• New Wood
• Viscosity of Supply	• 100 Seconds by Ford Cup B-4 at 30°C
• Shades Visible	• Pink
• Viscosity-of Application	• 40-45 Seconds
• Thinner recommended	• MTO
• Drying time	• Surface Dry-within 1 hours Hard Dry within 12 hours.
• Finish	• Matt and Smooth
• Flash point	• Above 30°C
• Covering Capacity	• 8-10 square meters per liter per coat depending on the surface.
• Directions For Use ¹	<ul style="list-style-type: none"> • :Ensure that new wood to be painted is free of moisture and loose particles. The surface should be brushed in properly to ensure that it is worked into the surface in order to prevent sinkage of gloss on the top coats of enamels applied • After drying of the surface and prior to the application of finishing paint, dry sand the surfacer with fine abrasive paper.