

Phn: +91-8009079988, 8009079977

Email: info@singhalpaints.com

SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

Sipcolite SpeedCoat Primer Surface Grey

Sipcolite speedcoat Primer surface grey, is unique & specially formulated universal product for use as a Primer-cum-surfacer on wood and metal both It can be used as an undercoat for Synthetic enamels, stoving Enamels & or nitrocellulose systems specially in coach finishing, truck show painting and other wood and metal finishing jobs, where quick drying properties are required.

• Surface to be Painted	:Metal and wood
• Shade available	:Grey
• Finish	:Matt
• Viscosity of supply	:80-100 seconds by Ford Cup No. B4 at 30°C.
• Flash Paint	:above 30°C.
• Method of Application	:Brush/Spray
• Viscosity of Application	:Brushing-60-65seconds Spraying 25-30 seconds at a pressure of 3.5Kg/Cms ² (40-45 psi)
• Drying time	:Surface dry within one hour hard dry within four hours. (The above varies with ambient temperature and humidity).
• Covering Capacity	:10-12 Sqr. Metres per coat depending on the surface.
• Thinners to be used	:Petrol & MTO
• Directions for use	:Ensure that the surface to be painted is free of grease, rust, moisture and looses particles. Wet cut the dried film with paper 320 to ensure proper adhesion of top finishing coat.

The information given here is given in good faith but without warranty, since conditions of use are beyond our control.