

Phn: +91-8009079988, 8009079977

Email: info@singhalpaints.com

SINGHAL PAINTS PRIVATE LIMITED

Off: N1-N6 Ancillary Estate Amausi Industrial Area, Nadarganj, Lucknow (UP)-226012 INDIA

Sipcolac Super Synthetic Clear Varnish

Sipcolac Super Synthetic clear Varnish is based on combination of high quality synthetic resins making it suitable as finishing varnish for wood and metal decoration on already painted Surfacers. It can also be used as mixing varnish with Sipcolac or Sipcolite Synthetic enamels to get mirror like finish.

Its attractive features are exterior durability, hardness, excellent gloss and gloss retention.

• Surfacers to be Painted	: Interior or exterior wooden & metal Surfacers.
• Viscosity of Supply	: 65±5 seconds by Ford Cup B4 at 30° C.
• Method of Application	: Brushing or spraying
• Drying Time	: Surface Dry Less than 2 hours Hard Dry Less than 12 hours (this property depends on the ambient temperature and humidity)
• Finish	: Smooth and glossy
• Flash point	: above 35°C.
• Directions for use	: Ensure that the surface to be painted is free from dust, grease or moisture. It can be thinned if necessary.

The information given here is given in good faith but without warranty, since conditions of use are beyond our control.